



## Poêle mixte à bois & à charbon, économique & efficace

### AVANTAGES :

To operate the stove, can use either wood logs or coal.

It is a wood stove in a very advantageous heating capacity for making powerful place in the room minimum.

With a smoke outlet vertical, wood burning and coal perfectly for residences.

**Nominal heat output :** 9 Kw

**Maximal thermal output :** 14 Kw

**Smoke outlet diameter :** 150 mm

**Flue gaz temperature :**

**Wood:** 322° - **Coal :** 310°

**Emission CO (13% Oxygen) :**

**Wood :** 0.3220 % - **Coal :** 0.3640 %

**Area covered :** 100 m<sup>2</sup>

**Finish stove :** thick plate

**Finish fireplace :** refractory bricks

**Energy efficiency :**

**Wood :** 67.45 % **Coal :** 68.05 %

**Fuel weight :**

**Wood :** 2.60 kg/h – **Coal :** 2.40 kg/h

**Dimensions :** L x P x H : 47 x 40 x 96 cm

**Net weight:** 78 kg **Color :** Grey

**Norm :** CE 13240 \* **European manufacturing**

**UPC Code :** 3700046513911

The stove is very simple and convenient. Use your choice of wood logs or coal, in the direction of the length to optimize space and maximum efficiency. With the power of 9 kW, this wood is amazing in its ability to heat.

The heating capacity of the stoves is high (67.45%), it ensures to recover over half of the heat produced by the wood stove. Thus, all the advantages of heating with wood in a traditional fireplace is provided without its drawbacks (evacuation inefficient spread of ash inside the room, bad combustion system, etc..).

To ensure the best possible functioning of the stove, it is recommended to be swept during and after the heating season.

To enjoy the quality of a fire similar to the traditional fireplace without the soot, because this wood stove is equipped with a drawer for collection of ashes.

**Distance to adjacent combustible materials :**

**Side & Rear :** 30 cm, **Front :** 80 cm

*\*Specifications subject to change without notice.*