



REVERSIBLE MONOBLOC AIR CONDITIONER ELECTRONIQUE WITH REMOTE CONTROL



FUNCTIONS

Mobile air conditioner. Requires no special installation. Warm air is evacuated through the air duct placed in the chink of a door or a window. Excellent to cool a middle size room $\pm 20 \text{ m}^2$.



Class : **A** - EER : 2.64



Area covered : room about $\pm 20\text{m}^2$



Cooling capacity : 2340 W - 8000 Btu/h



Warming power : 2340 W - 8000 Btu/h



Rated power consumption : 890 W



Warming absorbed power : 830 W



Air flow: 380 m^3/h



Speed : 3



Thermostat : electronic



Timer : 1 to 24 h.



Remote control



Water extraction : 24 L /day



Running from : 5°C to 32°C



Noise level : 44 to 55 dB



Refrigerant : R410A - 370 g



Unit dimensions :
LxPxH : 32 x 73 x 36 cm



Carton dimensions :
LxPxH : 38.4 x 87.2 x 41.2 cm



Net weight : 21 kg



Gross weight : 23 kg



Packaging: 1



UPC Code : 3700046513775



Norms : CE/GS



Voltage : 220/240 VAC 50 Hz



Finish : silver & grey

True heat pump

COP : 2.82

1000 W consumed = 2800 W

Heating power restored.

Class A - EER : 2.64

Easy moving on wheels.

With exhaust air duct.

1,50 m - ϕ 127 mm.